

# Steel Commercial Circulating Wall Fan 30 In. Black/Silver

**MODEL CCRF-30-W**

Facilities Maintenance / Commercial Circulator Fans

## PRODUCT OVERVIEW

The two speed, ball bearing, wall mount commercial circulating fan. These portable blowers do not have a totally enclosed motor. They should be used in a clean and dry commercial application. The guard is coated steel with retaining clips. The fan has a steel hub and aluminum paddle blades.

## KEY FEATURES

- Meets OSHA standards and is UL C/US listed
- Pull chain switch for easy use
- SJT type 3 conductor cord
- Motor is permanently lubricated with split capacitor



## CORE PRODUCT DATA

|                                                                                                                                                                             |                                                       |                                      |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|--------------------------------------|
| <b>ASSEMBLED WEIGHT</b><br><b>46 lbs</b>                                                                                                                                    | <b>ASSEMBLED SIZE</b><br><b>16" W x 36" L x 36" H</b> | <b>SHIP WEIGHT</b><br><b>46 lbs</b>  |
| <b>PACKAGE 1 SIZE</b><br><b>8" W x 29" D x 33" H</b>                                                                                                                        | <b>COLOR / FINISH</b><br><b>Black / Silver</b>        | <b>FREIGHT TYPE</b><br><b>Parcel</b> |
| <b>AVAILABILITY</b> Quote Required - Please Contact Sales<br>Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering. |                                                       | <b>QUICKSHIP: --</b>                 |

PRODUCT SPECIFICATIONS

|                             |                 |
|-----------------------------|-----------------|
| Blade Diameter (in.)        | 30              |
| Mounting Style              | Wall            |
| Amps High                   | 2.4             |
| CFM High                    | 6000            |
| CFM Low                     | 4800            |
| Electric Motor Horsepower   | 1/4             |
| Conductor Cord Length (in.) | 108             |
| Conductor Cord              | SJT type 3      |
| Voltage/Phase               | 115V/1PH        |
| CFM Medium                  | 5500            |
| OSHA                        | 1910.212 (a)(5) |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Gary, TN 37615

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=123>