

Steel Economical Foot Pump Drum Transporter 55 Gallon 1500 Lb. Capacity Yellow

MODEL DCR-880-H

Drum Handling Equipment / Economical Drum Transporters

PRODUCT OVERVIEW

Unique portable economical drum transporter is designed to lift and transport drums with a top lip. Steel jaw securely grips the top lip of the drum. Foot pump lift mechanism. Straddle legs rotate for access to drums on pallets. The push handle folds down for easy access to the foot pump.

KEY FEATURES

- Economical drum transporter design lifts and transports drums effectively
- Steel jaw securely grips the top lip of the drum for maximum efficiency
- Push handle folds down for easy access to the foot pump which lifts the drums
- Straddle legs rotate for access to drums on pallets for optimal results

CORE PRODUCT DATA

ASSEMBLED WEIGHT
269 lbs

ASSEMBLED SIZE
68.9375" W x 49.875" L x 43.625" H

SHIP WEIGHT
310 lbs

PACKAGE 1 SIZE
40" W x 48" D x 49" H

COLOR / FINISH
Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	1,500
Caster Quantity/Diameter/Width (in.)	(4) 8x2
Caster Material	Phenolic
Caster Type	Swivel
Operation	Foot Pump
Accepts	Steel, Plastic and Fiber Drums
Jaw Service Range (in. to in.)	31 to 48
Cradle Depth (in.)	3
Cradle Width (in.)	16-1/2
Cradle Height (in.)	2
Compatible Drum Size (gallon)	55
Number of Foot Pumps to Raise	22
Handle Height (in.)	40-1/2
Handle Diameter (in.)	1
Frame Height (in.)	43-5/8
Overall Raised Height (in.)	53-1/4
Maximum Overall Length (in.)	49-7/8
Minimum Overall Length (in.)	43-9/16
Maximum Overall Width (in.)	68-15/16
Minimum Overall Width (in.)	37-3/4
Maximum Inside Width (in.)	61-7/16
Minimum Inside Width (in.)	30-1/4

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=785>