

# Steel Folding Mezzanine Ladder with 115V Power Storage 120 In. Mezzanine Height 23-5/8 In. Step Width 350 Lb. Capacity Blue & Yellow

## MODEL LAD-FM-120-PSO

Industrial Ladders / Mezzanine Ladders (face mounted/retractable)



### PRODUCT OVERVIEW

The powered mezzanine ladders are used for infrequent usage to access mezzanines. They are quickly powered into climbing angle and back into stored position. The wheels roll on the ground when ratcheted, and the handrails mechanically rise into climb position when the ladder locks into position. Quickly extend and retract the ladder with the handheld pendant. The mezzanine ladder allows for quick installation. The unit keeps a small distance from the wall for compact storage. Customer must provide their mezzanine height at the time of purchase. Baked in powder coat blue and yellow finish for added toughness.

### KEY FEATURES

- Great for condensed work areas
- Treaded step design for sure footing
- Attached casters provide simple maneuvering
- Collapsible handrail

### CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
525.29 lbs

**ASSEMBLED SIZE**  
34.125" W x 83.6875" L x 152.25" H

**SHIP WEIGHT**  
514 lbs

**PACKAGE 1 SIZE**  
40" W x 128" D x 29" H

**COLOR / FINISH**  
Blue and Yellow

**FREIGHT TYPE**  
LTL Palletized

**AVAILABILITY** Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP:** --

### ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                  |                                       |
|----------------------------------|---------------------------------------|
| Base Length (in)                 | 83.6875                               |
| Base Width (in)                  | 34.125                                |
| ANSI Ladder Ratingc              | Type IA                               |
| Climbing Angle (degree)          | 58                                    |
| Steps                            | 13                                    |
| Distance Between Rung/Steps (in) | 9.25                                  |
| Rung/Step Width (in)             | 23.63                                 |
| Rung/Step Depth (in)             | 7                                     |
| Top Step Height From Ground (in) | 120.125                               |
| Rung/Step Material               | Serrated Steel                        |
| Number of Casters / Wheels       | 2                                     |
| Caster / Wheel Material          | Poly on Poly                          |
| Front Wheel Width (in)           | 1.25                                  |
| Front Wheel Diameter (in)        | 4                                     |
| Handrail Included                | Yes                                   |
| Handrail Height (in)             | 32.125                                |
| Spring Loaded                    | No                                    |
| OSHA Approved                    | Yes                                   |
| ANSI Approved                    | Yes                                   |
| Additional Contents              | AC Powered Mezzanine Ladder 115 Volts |
| Extended Height (in.)            | 152.25                                |
| Retracted Height (in.)           | 167.125                               |
| Max Capacity (lb.)               | 350                                   |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=611>