Molded Rubber Wheel Chock with Rope 8 In. x 56 In. x 4 In. Black

MODEL RWC-2-PR

Loading Dock Equipment / Rubber Wheel Chocks



PRODUCT OVERVIEW

The rubber wheel chocks are constructed of reinforced rubber to provide a sure grip on virtually any surface. The curved surface contours to fit tires. Rubber resists tearing, abrasion, ozone weathering, etc. The functional design includes a rope connected to the chock and is durable in all weather conditions.

KEY FEATURES

- Reinforced rubber resists tearing, abrasion and ozone weathering
- Functional design is durable in all weather conditions
- Rubber provides a sure grip on virtually any surface
- Curved surface contours to fit any tire style



CORE PRODUCT DATA

ASSEMBLED WEIGHT **7 lbs**	ASSEMBLED SIZE **5" W x 8.0625" L x 4.125" H**	SHIP WEIGHT **10 lbs**
PACKAGE 1 SIZE **7" W x 9" D x 5" H**	COLOR / FINISH **Black**	FREIGHT TYPE **Parcel**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Wheel Chock Connection	Rope
Wheel Chock Usage	Multi-Purpose
Built-In Handles / Poles	Yes
Grip Surface Material	Rubber
Wheel Chock Quantity	2
Usable Chock Width (in.)	5
Rope Length (in.)	56
Usable Chock Length (in.)	8-1/16
Usable Chock Height (in.)	4-1/8

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **30 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=79