

# Steel Trailer Stabilizing Spin Top Jack 26-5/8 In. x 17-5/8 In. x 39-1/2 In. 100,000 Lb. Static Capacity Yellow

## MODEL SP-TOP

Loading Dock Equipment / Trailer Stabilizing Jacks



### PRODUCT OVERVIEW

Trailer stabilizing jacks are used to prevent up-ending of semi-trailers when they are not connected to a tractor during loading and unloading operations. Throughout the loading and unloading process it is always recommended to use two jacks, one on each side of the front of the trailer. The trailer must be situated on a flat, stable and improved (preferably concrete) surface, while the jack sits perpendicular to the underside of the trailer. Every jack is built of a high strength steel construction with a flush-type Zerk fitting for lubricating ACME screw. A yellow powder coat finish and a reflective collar for visibility at night are both included. Each jack meets OSHA regulations when used with wheel chocks. \*\*The color of handles included with...

### KEY FEATURES

- Meets OSHA regulations when used with wheel chocks
- Round top plate
- Manual raising and lowering mechanism
- Reflective collar for great visibility at night

### CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**100 lbs**

ASSEMBLED SIZE  
**17.625" W x 26.625" L x 39.5" H**

SHIP WEIGHT  
**112 lbs**

PACKAGE 1 SIZE  
**30" W x 36" D x 45" H**

COLOR / FINISH  
**Yellow**

FREIGHT TYPE  
**LTL Palletized**

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                |             |
|--------------------------------|-------------|
| Uniform Static Capacity (lb.)  | 100,000     |
| Uniform Lifting Capacity (lb.) | 40,000      |
| Lowered Height (in.)           | 39-1/2      |
| Raised Height (in.)            | 51          |
| Wheel Size (in.)               | 10          |
| Wheel Type                     | Hard Rubber |
| Top Cap Diameter (in.)         | 8           |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=90>